

The SL2 tray sealer is the most **cost effective** and **versatile** machine in the range. **Environmentally efficient** and **reliable** the SL2 is the **ultimate** inline sealer.

# SL2 MAP-F

**VP** VERSATILE  
PACKAGING  
Keeping it Fresh



- Can seal up to 45 packs per minute
- Indisputable reliability
- Environmental considerations incorporated into design
- 2-minute tool changeovers
- Ultra-lightweight and quick release tooling
- Configurable for MAP-F
- High accuracy servo driven film feed system

# FRESH seal

## SL2



### FEATURES

#### Machine

- Operation from both sides
- Operator friendly touch screen provides machine status, self-diagnostics and operator prompts
- Pre-set accurate recipe-based temperature control
- High accuracy servo driven film feed system with easy to follow film path
- FSP (Film Snap Protection)
- Hygienic, robust construction to food industry standards
- Quick and easy to remove infeed and outfeed flat PU belt conveyors for added hygiene
- Film as thin as 17 mu can be used to reduce packaging waste
- Fully portable, caster mounted
- Can accept rotary top tools with modified bases and new transfer arms

#### Tooling

- Removable tooling impressions allow for continuous operation of the machine
- Two-minute tool changeover with quick release tools
- Lightweight tooling for manual loading
- Adjustable transfer arm heights cater for any depth of tray
- Quick release cutting blades
- Waterproof heater mats reduce failures during cleaning and reduce heat up times by up to 36%

#### Options


- MAP-F (Modified Atmosphere Packaging)
- Industrial remote access solution for remote diagnostics and program updates
- Eco-Cut™ - reducing film waste
- Foil crimping
- Inside cut for neater pack presentation
- Pre-printed or pre-punched registered film
- Through conveyor
- Date coder integration ready
- PCP (Pack Crush Protection) system

#### Service and Maintenance

All Packaging Automation machines are offered with a 12-month parts and labour warranty. A dedicated customer service team is ready to assist with service and maintenance calls and spare parts. Immediate technical phone support is available 24 hours a day 7 days a week.

#### Materials

The SL2 has the ability to heat seal reel fed film, pre-cut foil, paper or laminate lids to preformed trays and containers of CPET, polypropylene, PVC, styrene, board, smooth walled foil, pre-cut board, paper, plastic, foil lids and many other types of container.



### TECHNICAL INFORMATION

Height	1965mm
Length	2825mm
Width	910mm
Weight	750kg
Electrical supply	16A 415V 3 phase N+E 15A max/phase 50/60hz
Pneumatic supply	7.75cfm at 80psi (5.5 bar)
Production speed	15 cycles per minute

### TRAY LAYOUT OPTIONS AND THROUGHPUTS

MAXIMUM DIMENSIONS (MM)					
Number of trays	Length of tray	Width	Depth	Diameter (circular trays)	Production speed per min (up to)
1	470	300	120	300	15
2	300	222	120	222	30
3	300	140	120	140	45

